

12inch, 13inch, 15inch and 17inch Bezel Free Monitors



AerMonitor

We aim to exceed your expectations by providing high quality, reliable products with state of the art designs.

AerMonitor is a slim and elegant monitor that is offered with 12inch, 13inch, 15inch and 17 inch display options. It can either be wall mounted, or combined with a base or pole, giving a high level of flexibility that allows store owners to create the ideal system for specific application. The modular design features also ensures high serviceability and reliability.

Add-on Devices

All AerMonitor add-on devices use a USB interface for reliability, simple installation and maintenance.

USB I/O is on the right side of the display







OSD Controls: Display brightness, display power on/off



Power On/Off button & Status LED indicator for 13inch monitor




The adaptor is hidden inside the op




One-step operation for quick access to the add-on devices



The display can be easily removed for quick and efficient maintenance.



Various resolutions with different monitor size available.



Installation



Panel PC with integrated 12inch pole-type 2nd display



Panel PC with 12inch Aer-arm 2nd display



AerPOS with 12inch bracket 2nd display



Dual-Pole with 12inch & 15inch 2nd display

12.1inch Display	13.3inch Display	15inch Display	17inch Display
• 2 Resolution: 800 x 600, 1024 x 768 • 3 Brightness:330, 420, 450 nits	• Resolution: 1366 x 768 • Ratio: 16 : 10	• Resolution: 1024 x 768 • 2 Brightness: 350, 450 nits	Resolution: 1280 x 1024 • 2 Touch Panel: Resistive & P-Cap



434 x 405 x 297 mm, 4.6 Kg

Carton (W x H x D)





480 x 460 x 320 mm, 5.6 Kg



0	12inch Monitor			13inch Monitor							
Specifications						15inch Monitor				17inch Monitor	
Model	AM-1012A		AM-1012B		AM-1013A	AM-1013B	AM-101	5A	AM-10	15B	AM-1017
LCD Display Size	12.1" TFT LCD		13.3" TFT LCD		15" TFT LCD				17" TFT LCD		
Max. Resolution	800 x 600	1024 x 768	800 x 600	1024 x 768	1366 x 768		1024 x 768				1280 x 1024
Contrast Ratio	800:1	550:0	800:1	550:1	500:1		700 :1				1000:1
LCD Brightness (cd / m2)	330 / 450	500	330 / 450	500	200		350	450	350	450	250
Touch Screen	5-Wire Resis P-Capacitive		N/A		5-Wire Resistive N/A		5-Wire Resistive P-Capacitive Touch N/A			5-Wire Resistive P-Capacitive Touch	
Speaker	2 x 2W Speaker		N/A		N/A		2 x 2W Speaker		N/A		2 x 2W Speaker
Housing Color	Black with Silver Trim				Black		Black with Silver Trim				
Construction	Acrylonitrile Butadiene Styrene (ABS), Polycarbonate			Acrylonitrile Butadiene Styrene (ABS), Polycarbo					bonate		
I/O Ports											
Touch Screen Interface	1 x USB		N/A		1 x USB	N/A	1 x USB		N/A		1 x USB
Video Port	1 x VGA, 1 x DVI			1 x VGA, 1 x DVI		1 x VGA, 1 x DVI				1 x VGA, 1 x DVI	
Audio Port	1 x Line in		N/A		N/A		1 x Line i	n	N/A		1 x Line in
DC-in Port	1 x 2.5mm DC Jack			1 x 2.5mm DC Jack		1 x 2.5mm DC Jack				1 x 2.5mm DC Jack	
Power Supply	50W (12V / 4.16A) External Power Adaptor				50W (12V / 4.16A) External Pe			xternal Pow	ver Adaptor		
Dimensions & Weight											
Product (W x H x D)	Without Base: 308 x 248 x 39.7 mm, 2 Kg With Base: 308 x 308 x 212 mm, 3.6 Kg			Without Base: 351 x 220 x 31 mm, 1.6 Kg With Base: 351 x 303 x 212 mm, 3.2 Kg		Without Base: 367 x 315 x 35 mm, 2.5 Kg With Base: 367 x 315 x 195 mm, 4.2 Kg				Without Base: 410 x 332 x 39 mm, 3.8 Kg With Base: 410 x 382 x 212 mm, 5.5 Kg	

434 x 405 x 297 mm, 4.2 Kg

560 x 540 x 360 mm, 6.1 Kg *Specifications are subject to change without notice.